

Product Data Sheet

Product Description

GMCraft is asphalt saturated building paper, which is also described as a weather-resistive barrier, or moisture barrier. It is designed for installation behind stucco, and other exterior wall claddings as a "secondary weather barrier". **GMCraft** provides the needed protection from internal wall damage due to moisture leakage and condensation.

Products Standards

GMCraft 10 is a "weather-restrictive barrier" as described in Section 1404.2 of the 2000 International Building Code® (IBC) and also qualifies as a "weather-resistive sheathing paper" as described in Section R703 of the 2000 International Residential Code TM (IRC) - (and subsequent editions of these codes).

GMCraft 10 exceeds the standards set in Federal Specification UU-B-790a, Type 1, Grade "D", Style 2, in accordance with Section 1402.1 of the 1997 Uniform Building Code (and subsequent editions).

GMCraft 10 has maintained an ICC (formerly IBCO) Evaluation Report, since October of 2000 and satisfies test criteria for weather-resistive barriers (AC 38) dated July 2000. It currently has an approval until 2017 and **ESR # is 2376 meets 2012**, 2009 and 2006 International Building Code Requirements.

GMCraft 10 maintains ongoing testing to insure that it meets or exceeds industry standards (including ASTM D-779-03, ASTM D-828, and ASTM E-96-03). See typical results below.

Test Results

GMCraft 10	Test Method	Test Results	Industry Standard
Water Vapor	ASTM E-96-00	38 grams (+)	35 grams (min)
Transmission			
Water Resistance	ASTM D-779	Exceeds 20	10 minutes
		minutes	
Tensile Strength	ASTM D-828	MD 45 lb-f/in	MD 20lbf/in
		CD 21 lb-f/in	CD 20lbf/in

Physical Description

GMCraft 10 Single covers 324 SF and is 40" x 98 lineal feet. GMCraft 10 Double covers 162 SF and is 40" x 49 lineal feet.

Manufactured by GMC Roofing &Building Paper Products, INC. 6400 Zerker Road, Shafter, CA. 93263 (661) 399 4324