30 ASTM D 4869-05 TYPE II



"Authentic" Asphalt Saturated Organic Felt

A GREEN Roofing Product

Product Data

GMC 30 D 4869-05 TYPE II FELT is an industry leading, superior quality "authentic" asphalt saturated organic felt underlayment. Manufactured to ASTM 4869-05 type II specifications.

Certifications

ASTM D 4869-05, Type II

USES

GMC 30 D 4869-05 type II authentic asphalt saturated organic felt underlayment is used as a **breathable** secondary weather resistant barrier when applied over the roof deck prior to the installation of the primary roofing product.



Features and Benefits

Required Note: (Approved underlayment is required to validate warranty on most all roofing systems.)

• Compatible Recommended for use as an upgrade to 15 ASTM D 226 for asphalt shingle applications. May also be

used with other roofing systems when ASTM D 226 is not required.

• Easy to apply No special fasteners required. (Note: Plastic cap nails help seal around nail holes.)

• Cost effective Convenient roll size, 200sq. ft. coverage with salvage edge, minimizes job loss and excessive waste.

• **Permeable** Breathable membrane to help prevent dry rot, mold and other structural damages.

• Walk-able Natural non skid surface ideal for steep slope roofing.

• **Durable** Manufactured for maximum performance.

• Eco-friendly Organic dry felt is made from 100% post consumer recycled material and domestic asphalt from a local

source. Note: (Leed points may be available)

• USA Owned Jobs for local residents, good for the economy. GMC is a proud supporter of several national and local

and Operated charities.





Manufactured by GMC Roofing & Building Paper Products, INC. 6400 Zerker Road, Shafter, CA. 93263 (661) 399 4324

www.gmcpaper.com