

Pre-Tied Wire

- .ICC-ES ESR-1530 Certified ✓
- .Pre-tied angle clip & pin
- .Available in lengths of 2'- 20'
- .Packaged in bundles of 100pcs
- .Packaging also available in crates
- .Meets wire standard ASTM A641-92 ✓
- .See ceiling clip options below:



12 Gauge Pre-Tied Wire

Specification:

Wire Size: .105"
 Variation Tolerance: +/- .003"
 Tensile Range: 75ksi max.
 Zinc Thickness: ≥ 25g/m²
 Lengths available: 2', 3', 4', 6', 8' ... 20'
 Standard: ASTM A641-92 ✓



8 Gauge Pre-Tied Wire

Specification:

Wire Size: .162"
 Variation Tolerance: +/- .003"
 Tensile Range: 70ksi max.
 Zinc Thickness: ≥ 25g/m²
 Lengths available: 2', 3', 4', 6', 8' ... 20'
 Standard: ASTM A641-92 ✓

Powder Actuated Tools

- .Full line of powder actuated tools
- .Available in .27, .25 semi-auto & .22 single shot
- .Comparable to other PAT's in the market
- .Designed to meet the acoustical market demands
- .Tools work with all powder load brands currently available in the market

BP301 .27 Caliber



Semi-Automatic

BP35 .25 Caliber



Semi-Automatic

BP720 .22 Caliber



Single Shot

Powder Actuated Tool Loads

| Color | Green | Yellow | Red |
|-------|-------|--------|-----|
| Level | 3 | 4 | 5 |

- .27, .25 strip loads, .22 single shot & .25 disc loads
- .BP loads are designed to fit in other competitors' tools
- .Comparable to other loads in the market
- .Packaged in 100pcs per box

.27 Caliber



Strip Loads

.25 Caliber



Strip Loads

.22 Caliber



Single Shot Loads

.25 Caliber



Disc Loads

Angle Clip & Pin


- .Ceiling fasteners
- .Used for attachment of hanging applications
- .Available in a variety of clips and pin combinations
- .Standard carton 1,000 pcs
- .ICC-ES ESR-1530 Certified ✓



| MODEL # | DESCRIPTION |
|--------------|--------------------------------|
| PDAC90-25F10 | 1" pin with 90° angle clip |
| PDAC90-32F10 | 1-1/4" pin with 90° angle clip |



| MODEL # | DESCRIPTION |
|--------------|--------------------------------|
| PDAC45-25F10 | 1" pin with 45° angle clip |
| PDAC45-32F10 | 1-1/4" pin with 45° angle clip |



| MODEL # | DESCRIPTION |
|----------------|------------------------------|
| PDACTH90-22F10 | 7/8" pin with 90° angle clip |



| MODEL # | DESCRIPTION |
|---------|----------------|
| CL-1 | 90° angle clip |

Threaded Rod Fasteners

- .Threaded rod clips & fasteners
- .Fasten pre-assembled 1/4" threaded rod
- .Use Super Stud screws to hang 1/4 x 20 or 3/8 x 16 threaded rod
- .Installation into both wood and sheet metal
- .Standard carton 1,000 pcs

FR-ACP



Fast Rod 90 degree clip with 1-1/4" pin rivited 1/4x20 eye coupling

FR-AC



Fast Rod 90 degree clip rivited 1/4x20 eye coupling

| PART NO. | DESCRIPTION |
|---------------|---|
| 375 MC 200 SP | 3/8 X 16 rod coupling with 2" sharp point screw |
| 250 MC 150 SP | 1/4 X 20 rod coupling with 1.5" sharp point screw |
| 375 MC 750 SD | 3/8 X 16 rod coupling with 3/4" sharp point screw |
| 250 MN 750SD | 1/4 X 20 rod coupling with 3/4" sharp point screw |



PAT Fiberglass Extension Poles



Available in lengths of 6', 8', 10' & 12'

Affix branch contact information label here

Ph:877-779-2583
 www.bpfasteners.com