



BP-301



Highlights:

- 1) Highest reliability with very low maintenance
- 2) Padded recoil-absorbent handle to minimize effect to give operator great comfort
- 3) Engineered to provide safeness and excellent performance
- 4) Top performer and most reliable tool in the industry
- 5) Lightweight design to make jobs easier and lighter to carry around
- 6) Semi-automatic for quick response and getting the job done fastener
- 7) Fully loaded tool box including owners manual, cleaning equipment etc...
- 8) Replacement parts: Please see SPARE PARTS SECTION on website

Tech Specs:

- 1) Length: 13.39"
- 2) Weight: 5.07 LBS
- 3) Caliber Load: .27 10-shot strip Loads
- 4) Firing Action: Semi-Automatic
- 5) Pin Capacity: 1/2" - 2-1/2" (3" w/ washer)

Overview

The BP-301 is engineered and designed to be the most popular tool in the powder actuated industry. With its proven reliability performance and maximum comfort. This tool is a low velocity, semi-automatic .27 caliber tool that can be used to install .300 head pins, 8mm head drive pins and 1/4"-20 threaded studs, up to 3" in total length. This tool is designed for high speed use and repetitive applications throughout the contractors work hours.

Fastening Applications:

- 1) Acoustical Ceilings
- 5) Residential
- 2) Framing Works
- 6) Mechanical
- 3) Drywall Track
- 7) Ceiling Clip Assemblies
- 4) Electric al Applications
- 8) Concrete forms, basket clips, forming pins
- 9) Etc...

LOADS



.27 Caliber long strip for BP-301/BP-301A, POWERS® P3500/PA3500, RAMSET® SA270, VIPER, COBRA, HILTI® DX350, DX351, DX36M, DX451, SIMPSON® PT27, etc.

| MODEL NO. | CAT. NO. | DESCRIPTION | COLOR | POWER LEVEL | STD BOX | STD CTN | MASTER CTN |
|-----------|----------|-----------------------|--------|-------------|---------|---------|------------|
| 27LS11L6 | 131106 | .27 Cal 10-shot strip | Purple | strongest | 6 | 100 | 1,000 |
| 27LS11L5 | 131107 | .27 Cal 10-shot strip | Red | strong | 5 | 100 | 1,000 |
| 27LS11L4 | 131108 | .27 Cal 10-shot strip | Yellow | medium | 4 | 100 | 1,000 |
| 27LS11L3 | 131109 | .27 Cal 10-shot strip | Green | low | 3 | 100 | 1,000 |
| 27LS11L2 | 131110 | .27 Cal 10-shot strip | White | Lowest | 2 | 100 | 1,000 |

PINS



Compatible with other POWDER ACTUATED TOOLS

.300 Head Drive Pins:

Head Diameter: .300" / 7.6mm Shank Diameter: .145" / 3.7mm

| MODEL NO. | CAT. NO. | SHANK LENGTH | STD BOX | STD CTN |
|-----------|----------|--------------|---------|---------|
| *PD13F10K | 121101 | 1/2" Knurled | 13mm | 100 |
| PD19F10 | 121105 | 3/4" | 19mm | 100 |
| PD25F10 | 121109 | 1" | 25mm | 100 |
| PD32F10 | 121111 | 1-1/4" | 32mm | 100 |
| PD38F10 | 121113 | 1-1/2" | 38mm | 100 |
| PD44F10 | 121116 | 1-3/4" | 44mm | 100 |
| PD51F10 | 121119 | 2" | 51mm | 100 |
| PD63F10 | 121123 | 2-1/2" | 63mm | 100 |

.300 Head Drive Pins with Top Hat:

Head Diameter: .300" / 7.6 mm Shank Diameter: .145" / 3.7 mm

| MODEL NO. | CAT. NO. | SHANK LENGTH | STD BOX | STD CTN |
|-------------|----------|--------------|---------|---------|
| *PDTH13F10K | 121701 | 1/2" Knurled | 13mm | 100 |
| *PDTH16F10K | 121703 | 5/8" Knurled | 16mm | 100 |
| PDTH19F10 | 121705 | 3/4" | 19mm | 100 |
| PDTH25F10 | 121707 | 1" | 25mm | 100 |

*Fasteners for this tool: .300" and 8mm head, shank length from 1/2" up to 3" pins; 1/4"-20 thread studs etc.

*All compatible pins and loads from Ramset, Remington, Powers, Simpson, Hilti etc. will also fit the BP-301

.300 Head Drive Pins with 1" Washer:

Head Diameter: .300" / 7.6mm Shank Diameter: .145" / 3.7mm Washer Diameter: 1" / 25mm

| MODEL NO. | CAT. NO. | SHANK LENGTH | STD | STD CTN |
|-------------|----------|--------------|------|---------|
| PDW25-19F10 | 122001 | 3/4" | 19mm | 100 |
| PDW25-25F10 | 122003 | 1" | 25mm | 100 |
| PDW25-32F10 | 122005 | 1-1/4" | 32mm | 100 |
| PDW25-38F10 | 122007 | 1-1/2" | 38mm | 100 |
| PDW25-51F10 | 122009 | 2" | 51mm | 100 |
| PDW25-63F10 | 122011 | 2-1/2" | 63mm | 100 |
| PDW25-76F10 | 122013 | 3" | 76mm | 100 |

.300 Head Drive Pins with 3/4" Washer:

Head Diameter: .300" / 7.6mm Shank Diameter: .145" / 3.7mm Washer Diameter: 3/4" / 19mm

| MODEL NO. | CAT. NO. | SHANK LENGTH | STD | STD CTN |
|-------------|----------|--------------|------|---------|
| PDW19-19F10 | 122030 | 3/4" | 19mm | 100 |
| PDW19-25F10 | 122032 | 1" | 25mm | 100 |
| PDW19-32F10 | 122034 | 1-1/4" | 32mm | 100 |
| PDW19-38F10 | 122036 | 1-1/2" | 38mm | 100 |
| PDW19-51F10 | 122038 | 2" | 51mm | 100 |
| PDW19-63F10 | 122040 | 2-1/2" | 63mm | 100 |
| PDW19-76F10 | 122042 | 3" | 76mm | 100 |

.300 Head Drive Pins with 1-7/16" Insulation Washer :

Head Diameter: .300" / 7.6mm Shank Diameter: .145" / 3.7mm Washer Diameter: 36mm insulation washer

| MODEL NO. | CAT. NO. | SHANK LENGTH | STD | STD CTN |
|--------------|----------|--------------|------|---------|
| PDIW36-38F10 | 122054 | 1-1/2" | 38mm | 100 |
| PDIW36-51F10 | 122056 | 2" | 51mm | 100 |
| PDIW36-63F10 | 122058 | 2-1/2" | 63mm | 100 |
| PDIW36-76F10 | 122060 | 3" | 76mm | 100 |

BP-307

Highlights:

- 1) Semi-automatic piston returning
- 2) Semi-automatic powder load ejection
- 3) Low velocity piston drive tool adds safety to the job
- 4) Complete line of fasteners
- 5) Combines high performance and dependable productivity
- 6) Fully loaded tool box including owners manual, cleaning equipment etc...
- 7) Replacement parts: Please see SPARE PARTS SECTION on website

Tech Specs:

- 1) Length: 13.19"
- 2) Weight: 4.08 LBS
- 3) Caliber Load: .22 Single loads shot (all levels)
- 4) Firing Action: Single shot firing
- 5) Pin Capacity: 1/2" to 3"

Overview

The BP-307 is economically designed tool produces high productivity and dependable performance. This single shot firing tool makes it easy to operate and allows fast maintenance including easy repair in minutes. BP-307 handles all .300 and 8mm diameter headed drive pins from 1/2" to 3" shank lengths and 1/4" threaded studs.

Fastening Applications:

- 1) Drywall applications
- 2) General Purpose
- 3) Electrical
- 4) Residential
- 5) Metal Track
- 6) Concrete forms
- 7) Acoustical ceiling
- 8) Etc...

LOADS



.22 Caliber low velocity single shot loads can also be used for POWERS® P1000, P2201, P7201, RAMSET® 721, AND M70, HILT® DXE37 AND DXE72, SIMPSON® PT22, PT22H etc.

| MODEL NO. | CAT. NO. | DESCRIPTION | COLOR | POWER LEVEL | STD BOX | STD CTN | MASTER CTN | |
|-----------|----------|---------------------|--------|-------------|---------|---------|------------|--------|
| 22SGNDL4 | 131602 | .22 Cal single shot | Yellow | strong | 4 | 100 | 1,000 | 10,000 |
| 22SGNDL3 | 131603 | .22 Cal single shot | Green | medium | 3 | 100 | 1,000 | 10,000 |
| 22SGNDL2 | 131604 | .22 Cal single shot | Brown | low | 2 | 100 | 1,000 | 10,000 |
| 22SGNDL1 | 131605 | .22 Cal single shot | Gray | lowest | 1 | 100 | 1,000 | 10,000 |

PINS



Compatible with other POWDER ACTUATED TOOLS

.300 Head Drive Pins:

Head Diameter: .300" / 7.6mm Shank Diameter: .145" / 3.7mm

| MODEL NO. | CAT. NO. | SHANK LENGTH | STD BOX | STD CTN |
|-----------|----------|-------------------|---------|---------|
| *PD13F10K | 121101 | 1/2" Knurled 13mm | 100 | 5,000 |
| PD19F10 | 121105 | 3/4" 19mm | 100 | 5,000 |
| PD25F10 | 121109 | 1" 25mm | 100 | 5,000 |
| PD32F10 | 121111 | 1-1/4" 32mm | 100 | 1,000 |
| PD38F10 | 121113 | 1-1/2" 38mm | 100 | 1,000 |
| PD44F10 | 121116 | 1-3/4" 44mm | 100 | 1,000 |
| PD51F10 | 121119 | 2" 51mm | 100 | 1,000 |
| PD63F10 | 121123 | 2-1/2" 63mm | 100 | 1,000 |
| PD76F10 | 121125 | 3" 76mm | 100 | 1,000 |

.300 Head Drive Pins with Top Hat:

Head Diameter: .300" / 7.6mm Shank Diameter: .145" / 3.7mm

| | | | | | |
|-------------|--------|--------------|------|-----|-------|
| *PDTH13F10K | 121701 | 1/2" Knurled | 13mm | 100 | 5,000 |
| *PDTH16F10K | 121703 | 5/8" Knurled | 16mm | 100 | 5,000 |
| PDTH19F10 | 121705 | 3/4" | 19mm | 100 | 5,000 |
| PDTH25F10 | 121707 | 1" | 25mm | 100 | 5,000 |

*Fasteners for this tool: .300" and 8mm head, shank length from 1/2" up to 3" pins; 1/4"-20 thread studs etc.

*All compatible pins and loads from Ramset, Remington, Powers, Simpson, Hiltl etc. will also fit the BP-307

.300 Head Drive Pins with 1" Washer:

Head Diameter: .300" / 7.6mm Shank Diameter: .145" / 3.7mm Washer Diameter: 1" / 25mm

| MODEL NO. | CAT. NO. | SHANK LENGTH | STD | STD CTN |
|-------------|----------|--------------|-----|---------|
| PDW25-19F10 | 122001 | 3/4" 19mm | 100 | 1,000 |
| PDW25-25F10 | 122003 | 1" 25mm | 100 | 1,000 |
| PDW25-32F10 | 122005 | 1-1/4" 32mm | 100 | 1,000 |
| PDW25-38F10 | 122007 | 1-1/2" 38mm | 100 | 1,000 |
| PDW25-51F10 | 122009 | 2" 51mm | 100 | 1,000 |
| PDW25-63F10 | 122011 | 2-1/2" 63mm | 100 | 1,000 |
| PDW25-76F10 | 122013 | 3" 76mm | 100 | 1,000 |

.300 Head Drive Pins with 3/4" Washer:

Head Diameter: .300" / 7.6mm Shank Diameter: .145" / 3.7mm Washer Diameter: 3/4" / 19mm

| | | | | |
|-------------|--------|-------------|-----|-------|
| PDW19-19F10 | 122030 | 3/4" 19mm | 100 | 1,000 |
| PDW19-25F10 | 122032 | 1" 25mm | 100 | 1,000 |
| PDW19-32F10 | 122034 | 1-1/4" 32mm | 100 | 1,000 |
| PDW19-38F10 | 122036 | 1-1/2" 38mm | 100 | 1,000 |
| PDW19-51F10 | 122038 | 2" 51mm | 100 | 1,000 |
| PDW19-63F10 | 122040 | 2-1/2" 63mm | 100 | 1,000 |
| PDW19-76F10 | 122042 | 3" 76mm | 100 | 1,000 |

.300 Head Drive Pins with 1-7/16" Insulation Washer:

Head Diameter: .300" / 7.6mm Shank Diameter: .145" / 3.7mm Washer Diameter: 36mm insulation washer

| | | | | |
|--------------|--------|-------------|-----|-------|
| PDIW36-38F10 | 122054 | 1-1/2" 38mm | 100 | 1,000 |
| PDIW36-51F10 | 122056 | 2" 51mm | 100 | 1,000 |
| PDIW36-63F10 | 122058 | 2-1/2" 63mm | 100 | 1,000 |
| PDIW36-76F10 | 122060 | 3" 76mm | 100 | 1,000 |

BP-720

Highlights:

- 1) Rubber cushion grip for maximum comfort
- 2) Simple to maintain, saving time and money on labor cost
- 3) Tough housing makes it able to last for years
- 4) Automatic cartridge ejection system
- 5) Narrow 5/8" muzzle bushing for easy access in tight areas
- 6) Fully loaded tool box including owners manual, cleaning equipment etc...
- 7) Replacement parts: Please see SPARE PARTS SECTION on website

Tech Specs:

- 1) Length: 13.5"
- 2) Weight: 4.41 LBS
- 3) Caliber Load: .22 Single loads shot (all levels)
- 4) Firing Action: Single shot firing
- 5) Pin Capacity: 1/2" to 1-1/2"

Fastening Applications:

- 1) Drywall applications
- 2) General Purpose
- 3) Electrical
- 4) Residential
- 5) Metal Track
- 6) Concrete forms
- 7) Acoustical ceiling
- 8) Etc...

Overview

The **BP-720** low velocity single shot tool is designed to install ballistic point, .300 head drive pins, 8mm head drive pins and 1/4"-20 threaded studs up to 1-1/2" in total length. The tool has a balanced, simple design making operation and maintenance easy. Features include an automatic cartridge ejection system, a narrow 5/8" barrel which allows it to fit into tight areas and a rubber handle pad to minimize the effects of recoil.

LOADS



.22 Caliber low velocity single shot loads can also be used for **POWERS® P1000, P2201, P7201, RAMSET® 721, AND M70, HILT® DXE37 AND DXE72, SIMPSON® PT22, PT22H ETC.**

| MODEL NO. | CAT. NO. | DESCRIPTION | COLOR | POWER LEVEL | STD BOX | STD CTN | MASTER CTN |
|-----------|----------|---------------------|--------|-------------|---------|---------|------------|
| 22SGNDL4 | 131602 | .22 Cal single shot | Yellow | strong | 4 | 100 | 1,000 |
| 22SGNDL3 | 131603 | .22 Cal single shot | Green | medium | 3 | 100 | 1,000 |
| 22SGNDL2 | 131604 | .22 Cal single shot | Brown | low | 2 | 100 | 1,000 |
| 22SGNDL1 | 131605 | .22 Cal single shot | Gray | lowest | 1 | 100 | 1,000 |

PINS



Compatible with other POWDER ACTUATED TOOLS

.300 Head Drive Pins:

Head Diameter: .300" / 7.6mm Shank Diameter: .145" / 3.7mm

| MODEL NO. | CAT. NO. | SHANK LENGTH | STD BOX | STD CTN |
|-----------|----------|-------------------|---------|---------|
| *PD13F10K | 121101 | 1/2" Knurled 13mm | 100 | 5,000 |
| PD19F10 | 121105 | 3/4" 19mm | 100 | 5,000 |
| PD25F10 | 121109 | 1" 25mm | 100 | 5,000 |
| PD32F10 | 121111 | 1-1/4" 32mm | 100 | 1,000 |
| PD38F10 | 121113 | 1-1/2" 38mm | 100 | 1,000 |

.300 Head Drive Pins with Top Hat:

Head Diameter: .300" / 7.6 mm Shank Diameter: .145" / 3.7 mm

| | | | | | |
|-------------|--------|--------------|------|-----|-------|
| *PDTH13F10K | 121701 | 1/2" Knurled | 13mm | 100 | 5,000 |
| *PDTH16F10K | 121703 | 5/8" Knurled | 16mm | 100 | 5,000 |
| PDTH19F10 | 121705 | 3/4" | 19mm | 100 | 5,000 |
| PDTH25F10 | 121707 | 1" | 25mm | 100 | 5,000 |

| MODEL NO. | CAT. NO. | SHANK LENGTH | STD BOX | STD CTN |
|-----------|----------|--------------|---------|---------|
|-----------|----------|--------------|---------|---------|

.300 Head Drive Pins with 1" Washer:

Head Diameter: .300" / 7.6mm Shank Diameter: .145" / 3.7mm Washer Diameter: 1" / 25mm

| | | | | |
|-------------|--------|-------------|-----|-------|
| PDW25-32F10 | 122005 | 1-1/4" 32mm | 100 | 1,000 |
| PDW25-38F10 | 122007 | 1-1/2" 38mm | 100 | 1,000 |

.300 Head Drive Pins with 3/4" Washer:

Head Diameter: .300" / 7.6mm Shank Diameter: .145" / 3.7mm Washer Diameter: 3/4" / 19mm

| | | | | |
|-------------|--------|-----------|-----|-------|
| PDW19-19F10 | 122030 | 3/4" 19mm | 100 | 1,000 |
|-------------|--------|-----------|-----|-------|

.300 Head Drive Pins with 1-7/16" Insulation Washer:

Head Diameter: .300" / 7.6mm Shank Diameter: .145" / 3.7mm Washer Diameter: 36mm insulation washer

| | | | | |
|--------------|--------|-------------|-----|-------|
| PDIW36-38F10 | 122054 | 1-1/2" 38mm | 100 | 1,000 |
|--------------|--------|-------------|-----|-------|

*Fasteners for this tool: .300" and 8mm head drive pins and 1/4"-20 thread studs up to 1-1/2" in total length.

*All compatible pins and loads from Ramset & Powers will also fit the BP-720

BP-35

Highlights:

- 1) Engineered for Drywall and acoustical use
- 2) Semi-automatic and fast cycling
- 3) 10-shot .25 caliber loads for faster production
- 4) Fully loaded tool box including owners manual, cleaning equipment etc...
- 5) High reliability and low maintenance
- 6) Another tool nose piece available

Tech Specs:

- 1) Length: 11.42"
- 2) Weight: 4.3 LBS
- 3) Caliber Load: .25 10-shot strip Loads
- 4) Firing Action: Semi-Automatic
- 5) Pin Capacity: 1/2" - 1-1/2"

Fastening Applications:

- 1) Acoustical Applications
- 2) Drywall Applications
- 3) Clip to concrete
- 4) Wood to concrete
- 5) Wood to steel
- 6) Reliable and compact for short pin installation
- 7) much more...

Overview

The **BP-35** is specially designed for acoustical and drywall applications. The low velocity and semi-automatic tool can be used to install .300 head drive pins, 8mm head drive pins and 1/4" - 20 threaded studs up to 1-1/2" in total length. This tool is also engineered for high speed and repetitive volume applications to make you production run faster.

LOADS



Bluepoint .25 Caliber 10-shot strip loads can also be used for **POWERS® P35S**, **HILTI® DX35**, and **SIMPSON® PT-25S**

| MODEL NO. | CAT. NO. | DESCRIPTION | COLOR | POWER LEVEL | STD BOX | STD CTN | MASTER CTN |
|-----------|----------|-----------------------|--------|-------------|---------|---------|------------|
| 25SS10L5 | 131405 | .25 Cal 10-shot strip | Red | strong | 5 | 100 | 1,000 |
| 25SS10L4 | 131406 | .25 Cal 10-shot strip | Yellow | medium | 4 | 100 | 1,000 |
| 25SS10L3 | 131407 | .25 Cal 10-shot strip | Green | low | 3 | 100 | 1,000 |
| 25SS10L2 | 131408 | .25 Cal 10-shot strip | White | lowest | 2 | 100 | 1,000 |

PINS



Compatible with other POWDER ACTUATED TOOLS

.300 Head Drive Pins:

Head Diameter: .300" / 7.6mm Shank Diameter: .145" / 3.7mm

| MODEL NO. | CAT. NO. | SHANK LENGTH | STD BOX | STD CTN |
|-----------|----------|-------------------|---------|---------|
| *PD13F10K | 121101 | 1/2" Knurled 13mm | 100 | 5,000 |
| PD19F10 | 121105 | 3/4" 19mm | 100 | 5,000 |
| PD25F10 | 121109 | 1" 25mm | 100 | 5,000 |
| PD32F10 | 121111 | 1-1/4" 32mm | 100 | 1,000 |
| PD38F10 | 121113 | 1-1/2" 38mm | 100 | 1,000 |

.300 Head Drive Pins with Top Hat:

Head Diameter: .300" / 7.6 mm Shank Diameter: .145" / 3.7 mm

| | | | | |
|-------------|--------|-------------------|-----|-------|
| *PDTH13F10K | 121701 | 1/2" Knurled 13mm | 100 | 5,000 |
| *PDTH16F10K | 121703 | 5/8" Knurled 16mm | 100 | 5,000 |
| PDTH19F10 | 121705 | 3/4" 19mm | 100 | 5,000 |
| PDTH25F10 | 121707 | 1" 25mm | 100 | 5,000 |

| MODEL NO. | CAT. NO. | SHANK LENGTH | STD BOX | STD CTN |
|-----------|----------|--------------|---------|---------|
|-----------|----------|--------------|---------|---------|

.300 Head Drive Pins with 1" Washer:

Head Diameter: .300" / 7.6mm Shank Diameter: .145" / 3.7mm Washer Diameter: 1" / 25mm

| | | | | |
|-------------|--------|-------------|-----|-------|
| PDW25-32F10 | 122005 | 1-1/4" 32mm | 100 | 1,000 |
| PDW25-38F10 | 122007 | 1-1/2" 38mm | 100 | 1,000 |

.300 Head Drive Pins with 3/4" Washer:

Head Diameter: .300" / 7.6mm Shank Diameter: .145" / 3.7mm Washer Diameter: 3/4" / 19mm

| | | | | |
|-------------|--------|-----------|-----|-------|
| PDW19-19F10 | 122030 | 3/4" 19mm | 100 | 1,000 |
|-------------|--------|-----------|-----|-------|

.300 Head Drive Pins with 1-7/16" Insulation Washer:

Head Diameter: .300" / 7.6mm Shank Diameter: .145" / 3.7mm Washer Diameter: 36mm insulation washer

| | | | | |
|--------------|--------|-------------|-----|-------|
| PDIW36-38F10 | 122054 | 1-1/2" 38mm | 100 | 1,000 |
|--------------|--------|-------------|-----|-------|

*Fasteners for this tool: .300" and 8mm head, shank length from 1/2" up to 1-1/2" pins

*All compatible pins and loads from Powers & Hilti will also fit the BP-35

BP-450

Highlights:

- 1) Faster production and high reliability
- 2) The most suitable for ball headed and threaded studs installation.
- 3) Silent enough to use indoors
- 4) Automatic cartridge feed
- 5) Engineered for better accuracy during installation of pins.
- 6) Fully loaded tool box including owners manual, cleaning equipment etc...

Tech Specs:

- 1) Length: 11.42"
- 2) Weight: 4.3 LBS
- 3) Caliber Load: .27 10-shot strip loads
- 4) Firing Action: Automatic
- 5) Pin Capacity: <8mm

Fastening Applications:

- 1) Drywall applications
- 2) General Purpose
- 3) Electrical
- 4) Residential
- 5) Metal Track
- 6) Concrete forms
- 7) Acoustical ceiling
- 8) Etc...

Overview

BP-450 is a fully designed automatic powder actuated tool that is the most versatile and fastest powder tool system out there. The product works fast and is completely automatic. Only weighing at a bit over 4 lbs this heavy duty tool can get the job done without exhausting yourself. This tool is also suitable indoors due to the low velocity this tool puts out. This tool provides durable construction and proven dependability.

LOADS



.27CAL LONG STRIP LOADS

| MODEL NO. | CAT. NO. | DIAMETER-LENGTH | COLOR | POWER LEVEL |
|-----------|----------|-----------------|--------|-------------|
| 27LS11L6 | 131106 | .27cal,.6.8"11 | Purple | strongest 6 |
| 27LS11L5 | 131107 | .27cal,.6.8"11 | Red | strong 5 |

PINS



8mm Head Drive Pins:

Head Diameter: 8mm Shank Diameter: .145" / 3.7mm

| MODEL NO. | CAT. NO. | SHANK LENGTH | STD BOX | STD CTN |
|-----------|----------|------------------|---------|---------|
| DN13P8K | 121201 | 13mm 1/2"Knurled | 100 | 1,000 |
| DN19P8 | 121203 | 19mm 3/4" | 100 | 1,000 |
| DN22P8 | 121205 | 22mm 7/8" | 100 | 1,000 |
| DN27P8 | 121207 | 27mm 1" | 100 | 1,000 |
| DN32P8 | 121209 | 32mm 1-1/4" | 100 | 1,000 |
| DN37P8 | 121211 | 37mm 1-1/2" | 100 | 1,000 |
| DN42P8 | 121213 | 42mm 1-3/4" | 100 | 1,000 |
| DN47P8 | 121215 | 47mm 1-7/8" | 100 | 1,000 |
| DN52P8 | 121217 | 52mm 2" | 100 | 1,000 |
| DN57P8 | 121219 | 57mm 2-1/4" | 100 | 1,000 |
| DN62P8 | 121221 | 62mm 2-1/2" | 100 | 1,000 |
| DN72P8 | 121223 | 72mm 2-7/8" | 100 | 1,000 |

8mm Head Drive Pins with Top Hat:

Head Diameter: 8mm Shank Diameter: .145" / 3.7mm

| | | | | |
|------------|--------|------------------|-----|-------|
| *DNTH16P8K | 121803 | 16mm 5/8"Knurled | 100 | 1,000 |
| DNTH19P8 | 121805 | 19mm 3/4" | 100 | 1,000 |
| DNTH25P8 | 121807 | 25mm 1" | 100 | 1,000 |

5.7mm dia. Head Drive Pins:

Head Diameter: 5.7mm Shank Diameter: .145" / 3.7mm Washer Diameter: 12mm

| | | | | |
|----------|--------|------------------|-----|-------|
| NK16W12K | 121501 | 16mm 5/8"Knurled | 100 | 1,000 |
| NK19W12K | 121503 | 19mm 3/4"Knurled | 100 | 1,000 |
| NK27W12 | 121509 | 27mm 1" | 100 | 1,000 |
| NK32W12 | 121511 | 32mm 1-1/4" | 100 | 1,000 |
| NK37W12 | 121513 | 37mm 1-1/2" | 100 | 1,000 |

STUDS

1/4"-20 Treaded Studs:

Thread Size: 1/4"-20 Shank Diameter: .145" Plastic Cap Diameter: 8mm

| MODEL NO. | CAT. NO. | THREAD LENGTH | SHANK LENGTH | STD. BOX | STD. CARTON |
|------------------|----------|---------------|------------------|----------|-------------|
| M1/4PH-13-13F10K | 123401 | 13mm 1/2" | 1/2"Knurled 13mm | 100 | 1,000 |
| M1/4PH-13-19F10 | 123403 | 13mm 1/2" | 3/4" 19mm | 100 | 1,000 |
| M1/4PH-13-25F10 | 123405 | 13mm 1/2" | 1" 25mm | 100 | 1,000 |
| M1/4PH-13-32F10 | 123407 | 13mm 1/2" | 1-1/4" 32mm | 100 | 1,000 |
| M1/4PH-19-13F10K | 123409 | 19mm 3/4" | 1/2"Knurled 25mm | 100 | 1,000 |
| M1/4PH-19-19F10 | 123411 | 19mm 3/4" | 3/4" 19mm | 100 | 1,000 |
| M1/4PH-19-25F10 | 123413 | 19mm 3/4" | 1" 25mm | 100 | 1,000 |
| M1/4PH-19-32F10 | 123415 | 19mm 3/4" | 1-1/4" 32mm | 100 | 1,000 |
| M1/4PH-25-25F10 | 123417 | 25mm 1" | 1" 25mm | 100 | 1,000 |
| M1/4PH-32-13F10K | 123419 | 32mm 1-1/4" | 1/2"Knurled 13mm | 100 | 1,000 |
| M1/4PH-32-32F10 | 123421 | 32mm 1-1/4" | 1-1/4" 32mm | 100 | 1,000 |

3/8"-16 Treaded Studs:

Thread Size: 3/8"-16 Shank Diameter: .205" Thread Length: 1-1/4"

| MODEL NO. | CAT. NO. | SHANK LENGTH | STD. BOX | STD. CARTON |
|----------------|----------|--------------|----------|-------------|
| M3/8-32-19F10K | 123509 | 3/4"Knurled | 100 | 1,000 |
| M3/8-32-25F10 | 123511 | 1" | 100 | 1,000 |
| M3/8-32-32F10 | 123513 | 1-1/4" | 100 | 1,000 |

*Fasteners for this tool:

- 1) 5.7mm head, shank length up to 3" with 12mm washer pins
- 2) .300" and 8mm head, shank length from 1/2" up to 3" pins; 1/4"-20 thread studs
- 3) 10mm head shank length up to 3" pins; 3/8"-16 thread studs
- 4) TB Eyelet pins for concrete

*All compatible pins and loads from Ramset, Remington, Powers, Simpson, Hitli etc. will also fit the BP-450


DRIVE PINS

.300 Head Drive Pins

Standard Pins:

Head Diameter: .300" / 7.6mm Shank Diameter: .145" / 3.7mm

| MODEL NO. | CAT. NO. | SHANK LENGTH | STD BOX | STD CTN | |
|-----------|----------|--------------|---------|---------|-------|
| *PD13F10K | 121101 | 1/2"Knurled | 13mm | 100 | 5,000 |
| PD19F10 | 121105 | 3/4" | 19mm | 100 | 5,000 |
| PD25F10 | 121109 | 1" | 25mm | 100 | 5,000 |
| PD32F10 | 121111 | 1-1/4" | 32mm | 100 | 1,000 |
| PD38F10 | 121113 | 1-1/2" | 38mm | 100 | 1,000 |
| PD44F10 | 121116 | 1-3/4" | 44mm | 100 | 1,000 |
| PD51F10 | 121119 | 2" | 51mm | 100 | 1,000 |
| PD63F10 | 121123 | 2-1/2" | 63mm | 100 | 1,000 |
| PD76F10 | 121125 | 3" | 76mm | 100 | 1,000 |





Top Hat Pins:

.300 Head Drive Pins with Top Hat:

Head Diameter: .300" / 7.6 mm Shank Diameter: .145" / 3.7 mm

| | | | | | |
|-------------|--------|--------------|------|-----|-------|
| *PDTH13F10K | 121701 | 1/2" Knurled | 13mm | 100 | 5,000 |
| *PDTH16F10K | 121703 | 5/8" Knurled | 16mm | 100 | 5,000 |
| PDTH19F10 | 121705 | 3/4" | 19mm | 100 | 5,000 |
| PDTH25F10 | 121707 | 1" | 25mm | 100 | 5,000 |




* K is knurled shank

* 8mm head pins with top hats are available

Washer Pins:

Head Diameter: .300" / 7.6mm Shank Diameter: .145" / 3.7mm Washer Diameter: 3/4"; 7/8"; 1" / 25mm

| | | | | | |
|-------------|--------|--------|------|-----|-------|
| PDW25-19F10 | 122001 | 3/4" | 19mm | 100 | 1,000 |
| PDW25-25F10 | 122003 | 1" | 25mm | 100 | 1,000 |
| PDW25-32F10 | 122005 | 1-1/4" | 32mm | 100 | 1,000 |
| PDW25-38F10 | 122007 | 1-1/2" | 38mm | 100 | 1,000 |
| PDW25-51F10 | 122009 | 2" | 51mm | 100 | 1,000 |
| PDW25-63F10 | 122011 | 2-1/2" | 63mm | 100 | 1,000 |
| PDW25-76F10 | 122013 | 3" | 76mm | 100 | 1,000 |



* Pins with 1" x 1" and other size washers are available

* All sizes of washer pin for ACQ treated lumber wood are available

Head Diameter: .300" / 7.6mm

Shank Diameter: .145" / 3.7mm

Washer Diameter: 1-7/16" / 36mm insulation washer

| | | | | | |
|--------------|--------|--------|------|-----|-------|
| PDIW36-38F10 | 122054 | 1-1/2" | 38mm | 100 | 1,000 |
| PDIW36-51F10 | 122056 | 2" | 51mm | 100 | 1,000 |
| PDIW36-63F10 | 122058 | 2-1/2" | 63mm | 100 | 1,000 |
| PDIW36-76F10 | 122060 | 3" | 76mm | 100 | 1,000 |



* 8mm head pins with insulation washers are available

Angle Clip Pins:

Head Diameter: .300" / 7.6mm

Shank Diameter: .145" / 3.7mm Angle Clip: 90°, dome

| MODEL NO. | CAT. NO. | SHANK LENGTH | | STD BOX | STD CTN |
|--------------|----------|--------------|------|---------|---------|
| PDAC90-25F10 | 122502 | 1" | 25mm | 100 | 1,000 |
| PDAC90-32F10 | 122504 | 1-1/4" | 32mm | 100 | 1,000 |

* 8mm head angle clip pin is available

Head Diameter: .300" / 7.6mm

Shank Diameter: .145" / 3.7mm

Angle Clip: 120°, dome


| | | | | | |
|---------------|--------|--------|------|-----|-------|
| PDAC120-25F10 | 122502 | 1" | 25mm | 100 | 1,000 |
| PDAC120-32F10 | 122504 | 1-1/4" | 32mm | 100 | 1,000 |



Head Diameter: .300" / 7.6mm

Shank Diameter: .145" / 3.7mm Angle Clip: 90° with top hat

| | | | | |
|---------------|--------|--------|-----|-------|
| PDACTH9025F10 | 122411 | 1" | 100 | 1,000 |
| PDACTH9032F10 | 122413 | 1 1/4" | 100 | 1,000 |
| PDACTH9022F10 | | 7/8" | 100 | 1,000 |



* 8mm head angle clip pin is available

Conduit Clip Pins:

.300 Head Drive Pins with Conduit Clips

Head Diameter: .300" / 7.6mm Shank Diameter: .145" / 3.7mm

| MODEL NO. | CAT. NO. | CLIP SIZE | SHANK LENGTH | STD BOX | STD CTN |
|---------------|----------|-----------|--------------|---------|---------|
| PDCC50-25F10 | 122620 | 1/2" | 1" | 100 | 1,000 |
| PDCC50-32F10 | 122621 | 1/2" | 1-1/4" | 100 | 1,000 |
| PDCC75-25F10 | 122630 | 3/4" | 1" | 100 | 1,000 |
| PDCC75-32F10 | 122631 | 3/4" | 1-1/4" | 100 | 1,000 |
| PDCC100-25F10 | 122640 | 1" | 1" | 100 | 1,000 |
| PDCC100-32F10 | 122641 | 1" | 1-1/4" | 100 | 1,000 |



8mm Head Drive Pins

Standard Pins:

Head Diameter: 8mm Shank Diameter: .145" / 3.7mm

| MODEL NO. | CAT. NO. | SHANK LENGTH | STD. BOX | STD. CTN |
|-----------|----------|--------------|----------|----------|
| DN13P8 | 121201 | 13mm | 100 | 1,000 |
| DN19P8 | 121203 | 19mm | 100 | 1,000 |
| DN22P8 | 121205 | 22mm | 100 | 1,000 |
| DN27P8 | 121207 | 27mm | 100 | 1,000 |
| DN32P8 | 121209 | 32mm | 100 | 1,000 |
| DN37P8 | 121211 | 37mm | 100 | 1,000 |
| DN42P8 | 121213 | 42mm | 100 | 1,000 |
| DN47P8 | 121215 | 47mm | 100 | 1,000 |
| DN52P8 | 121217 | 52mm | 100 | 1,000 |
| DN57P8 | 121219 | 57mm | 100 | 1,000 |
| DN62P8 | 121221 | 62mm | 100 | 1,000 |
| DN72P8 | 121223 | 72mm | 100 | 1,000 |

* With different size washers are available

Top Hat Pins:

Head Diameter: 8mm Shank Diameter: .145" / 3.7mm

| | | | | | |
|------------|--------|--------------|------|-----|-------|
| *DNTH16P8K | 121803 | 5/8" Knurled | 16mm | 100 | 1,000 |
| DNTH19P8 | 121805 | 3/4" | 19mm | 100 | 1,000 |
| DNTH25P8 | 121807 | 1" | 25mm | 100 | 1,000 |

Top Hat Angle Clip Pins:

Head Diameter: 8mm

Shank Diameter: .145" / 3.7mm Angle Clip: 90°, with top hat

| | | | | |
|------------|--------|--------|-----|-------|
| DNACTH27P8 | 122701 | 1" | 100 | 1,000 |
| DNACTH32P8 | 122702 | 1-1/4" | 100 | 1,000 |



5.7mm Head Drive Pins

Standard Pins:

Head Diameter: 5.7mm Shank Diameter: .145" / 3.7mm Washer Diameter: 12mm

| | | | | | |
|-----------|--------|--------------|------|-----|-------|
| *NK16W12K | 121501 | 5/8" knurled | 16mm | 100 | 1,000 |
| *NK19W12K | 121503 | 3/4" knurled | 19mm | 100 | 1,000 |
| NK27W12 | 121509 | 1" | 27mm | 100 | 1,000 |
| NK32W12 | 121511 | 1-1/4" | 32mm | 100 | 1,000 |
| NK37W12 | 121513 | 1-1/2" | 37mm | 100 | 1,000 |



Pinch Point Ridge



Ballistic Point (no ridge)



Pinch Point Ridge






Product Info:

All of Bluepoint pins are ballistic not pinch point, which means that Bluepoint's pins are made of better quality and offered at lower price. The Competition sells pinch point pins which is inexpensive to make and they charge a whole lot more for the product. Just look at the tips!



THREADED STUDS

| THREADED STUDS | | | | | | | | | |
|---|----------|---------------|--------------|--------------|----------|---|--|----------|----------|
| Plastic Cap Threaded Studs: Thread Size: 1/4"-20 Shank Diameter: .145" Plastic Cap Diameter: 8mm | | | | | |  | | | |
| MODEL NO. | CAT. NO. | THREAD LENGTH | | SHANK LENGTH | | | | STD. BOX | STD. CTN |
| M1/4PH-13-13F10K | 123401 | 1/2" | 13mm | 1/2"Knurled | 13mm | | | 100 | 1,000 |
| M1/4PH-13-19F10 | 123403 | 1/2" | 13mm | 3/4" | 19mm | | | 100 | 1,000 |
| M1/4PH-13-25F10 | 123405 | 1/2" | 13mm | 1" | 25mm | | | 100 | 1,000 |
| M1/4PH-13-32F10 | 123407 | 1/2" | 13mm | 1-1/4" | 32mm | | | 100 | 1,000 |
| M1/4PH-19-13F10K | 123409 | 3/4" | 19mm | 1/2" Knurled | 25mm | | | 100 | 1,000 |
| M1/4PH-19-19F10 | 123411 | 3/4" | 19mm | 3/4" | 19mm | | | 100 | 1,000 |
| M1/4PH-19-25F10 | 123413 | 3/4" | 19mm | 1" | 25mm | | | 100 | 1,000 |
| M1/4PH-19-32F10 | 123415 | 3/4" | 19mm | 1-1/4" | 32mm | | | 100 | 1,000 |
| M1/4PH-25-25F10 | 123417 | 1" | 25mm | 1" | 25mm | | | 100 | 1,000 |
| M1/4PH-32-13F10K | 123419 | 1-1/4" | 32mm | 1/2" Knurled | 13mm | | | 100 | 1,000 |
| M1/4PH-32-32F10 | 123421 | 1-1/4" | 32mm | 1-1/4" | 32mm | | | 100 | 1,000 |
| 3/8"-16 Threaded Studs: Thread Size: 3/8"-16(10mm) Shank Diameter: .205" Thread Length: 1-1/4" | | | | | |  | | | |
| MODEL NO. | CAT. NO. | SHANK LENGTH | STD BOX | STD CTN | | | | | |
| *M3/8-32-19F10K | 123509 | 3/4"Knurled | 100 | 1,000 | | | | | |
| M3/8-32-25F10 | 123511 | 1" | 100 | 1,000 | | | | | |
| M3/8-32-32F10 | 123513 | 1-1/4" | 100 | 1,000 | | | | | |
| Double Washer Threaded Studs: Thread Size: 1/4"-20 (6MM) Shank Diameter: .145" (3.7MM) Washer Size: 12mm | | | | | |  | | | |
| MODEL NO. | CAT. NO. | THREAD LENGTH | SHANK LENGTH | STD. BOX | STD. CTN | | | | |
| *M1/4-12-12P12K | 123600 | 1/2" | 11MM | 1/2"Knurled | 12mm | | | 100 | 1,000 |
| *M1/4-20-12P12K | 123601 | 3/4" | 20MM | 1/2"Knurled | 12mm | | | 100 | 1,000 |
| M6-20-27P12 | 123602 | 3/4" | 20MM | 1" | 25mm | | | 100 | 1,000 |
| M6-20-32P12 | 123603 | 3/4" | 20MM | 1-1/4" | 32mm | | | 100 | 1,000 |
| M6-32-32P12 | 123604 | 1-1/4" | 32MM | 1-1/4" | 32mm | | | 100 | 1,000 |

HANGING SYSTEMS

| OTHER ACCESSORIES: | | | | |
|--------------------|----------|---|-------------|---|
| FR-AC | | | | |
| MEDEL NO. | CAT. NO. | DESCRIPTION | STADARD BOX | |
| FR1/4-AC | 125030 | Fast Rod 90 degree clip rivoted 1/4x20 eye coupling | 100 |  |
| FR-ACP | | | | |
| FR1/4-ACP32 | 125033 | Fast Rod 90 degree clip with 1-1/4" pin rivited 1/4x20 eye coupling | 100 |  |
| FR-ZC | | | | |
| FR1/4-ZC | 125040 | Fast Rod "Z" clip - Plain Z Clip with 1/4-20 threaded hole | 100 |  |

MALE COUPLERS SCREWS

| SPECIAL SCREWS: | | | |
|-----------------|----------|---|-------------|
| MEDEL NO. | CAT. NO. | DESCRIPTION | STADARD BOX |
| 375MC200SP | 125060 | 3/8 x 16 rod coupling with 2" sharp point screw | 100 |
| 250 MC 150 SP | 125062 | 1/4 X 20 rod coupling with 1.5" sharp point screw | 100 |
| 375 MC 750 SD | 125064 | 3/8 x 16 rod coupling with 3/4" sharp point screw | 100 |
| 250 MC 750SD | 125066 | 1/4 x 20 rod coupling with 3/4" sharp point screw | 100 |

POWERLOADS

Tested and compared to the competition for:

-Residue (cleanliness) -Consistency of power levels -Miss fires(Firing Consistency)

Bluepoint out performed the competition!

POWERLOADS

.22cal straight wall single shot loads

| MODEL NO. | CAT. NO. | SPECIFICATION | COLOR | POWER | POWER LEVEL |
|-----------|----------|------------------------------|--------|--------|-------------|
| 22SGSWL6 | 131701 | .22cal. 5.6*15 Straight Wall | Purple | Strong | 6 |
| 22SGSWL5 | 131702 | .22cal. 5.6*15 Straight Wall | Red | Medium | 5 |
| 22SGSWL4 | 131703 | .22cal. 5.6*15 Straight Wall | Yellow | Low | 4 |
| 22SGSWL3 | 131704 | .22cal. 5.6*15 Straight Wall | Green | Lowest | 3 |



.22cal neck down single shot loads

| | | | | | |
|----------|--------|--------------------------|--------|-----------|---|
| 22SGNDL5 | 131601 | .22cal. 5.6*16 Neck down | Red | strongest | 5 |
| 22SGNDL4 | 131602 | .22cal. 5.6*16 Neck down | Yellow | strong | 4 |
| 22SGNDL3 | 131603 | .22cal. 5.6*16 Neck down | Green | medium | 3 |
| 22SGNDL2 | 131604 | .22cal. 5.6*16 Neck down | Brown | low | 2 |
| 22SGNDL1 | 131605 | .22cal. 5.6*16 Neck down | Gray | lowest | 1 |




.25cal strip loads

| | | | | | |
|----------|--------|----------------|--------|--------|---|
| 25SS10L5 | 131405 | .25cal. 6.3*10 | Red | strong | 5 |
| 25SS10L4 | 131406 | .25cal. 6.3*10 | Yellow | medium | 4 |
| 25SS10L3 | 131407 | .25cal. 6.3*10 | Green | low | 3 |
| 25SS10L2 | 131408 | .25cal. 6.3*10 | White | lowest | 2 |



.25 Cal metal disc loads

| | | | | | |
|----------|--------|----------------|--------|--------|---|
| 25MD10L5 | 131409 | .25cal. 6.3*10 | Red | strong | 5 |
| 25MD10L4 | 131410 | .25cal. 6.3*10 | Yellow | medium | 4 |
| 25MD10L3 | 131411 | .25cal. 6.3*10 | Green | low | 3 |
| 25MD10L2 | 131412 | .25cal. 6.3*10 | White | lowest | 2 |



.27cal long strip loads

| | | | | | |
|----------|--------|-----------------|--------|-----------|---|
| 27LS11L6 | 131106 | .27cal., 6.8*11 | Purple | strongest | 6 |
| 27LS11L5 | 131107 | .27cal., 6.8*11 | Red | strong | 5 |
| 27LS11L4 | 131108 | .27cal., 6.8*11 | Yellow | medium | 4 |
| 27LS11L3 | 131109 | .27cal., 6.8*11 | Green | low | 3 |
| 27LS11L2 | 131110 | .27cal., 6.8*11 | White | Lowest | 2 |



HANGING SYSTEMS

HOOKS AND HANGERS

T Hooks:

| MODEL NO. | CAT. NO. | HOOK SIZE | LOAD CAPACITY | STD. BOX |
|-----------|----------|-----------|---------------|----------|
| TH12 | 125301 | 3/4" | 12lbs | 100 |
| TH21 | 125302 | 1-5/16" | 17lbs | 100 |
| TH32 | 125303 | 2" | 17lbs | 100 |
| TH64 | 125304 | 4" | 50lbs | 25 |



CCM Hooks:

| | | | | |
|-------|--------|---------|-------|-----|
| CCM12 | 125401 | 3/4" | 12lbs | 100 |
| CCM21 | 125402 | 1-5/16" | 17lbs | 100 |
| CCM32 | 125403 | 2" | 17lbs | 100 |
| CCM64 | 125404 | 4" | 50lbs | 25 |



CCP Hooks:

| | | | | |
|-------|--------|---------|-------|-----|
| CCP12 | 125501 | 3/4" | 12lbs | 100 |
| CCP21 | 125502 | 1-5/16" | 17lbs | 100 |
| CCP32 | 125503 | 2" | 17lbs | 100 |
| CCP64 | 125504 | 4" | 50lbs | 25 |



ACCESSORIES FOR HOOKS

| NAME | CAT. NO. | STD. BOX | |
|--------------|----------|----------|---|
| W-Bat wing | 125000 | 100 |  |
| Angle Clip | 125001 | 100 |  |
| Eye Coupling | 125002 | 100 |  |
| HOK-24 | 125003 | 100 |  |
| HOK-58 | 125004 | 100 |  |
| ADOC-14 | 125010 | 100 |  |

| NAME | CAT. NO. | STD. BOX | |
|----------|----------|----------|---|
| PBC | 125007 | 100 |  |
| ACHOK-24 | 125005 | 100 |  |
| ACHOK-58 | 125006 | 100 |  |
| ACBPC | 125008 | 100 |  |
| VOH-14 | 125009 | 100 |  |

PRE-TIED WIRE

PRE-TIED STRAIGHT CUT WIRES

Wire Specification: 12 gage galvanized soft straight cut wires
Pin Specification: .300" / 7.6mm head, .145" / 3.7mm shank Angle Clip Specification: 90° with dome

| MODEL NO. | CAT. NO. | SHANK LENGTH | WIRE LENGTH | QTY./ BUNDLE |
|-----------|----------|--------------|-------------|--------------|
| WR04AC25 | 124504 | 1" | 4' | 100 |
| WR06AC25 | 124506 | 1" | 6' | 100 |
| WR08AC25 | 124508 | 1" | 8' | 100 |
| WR10AC25 | 124510 | 1" | 10' | 100 |
| WR12AC25 | 124512 | 1" | 12' | 100 |
| WR04AC32 | 124524 | 1-1/4" | 4' | 100 |
| WR06AC32 | 124526 | 1-1/4" | 6' | 100 |
| WR08AC32 | 124528 | 1-1/4" | 8' | 100 |
| WR10AC32 | 124530 | 1-1/4" | 10' | 100 |
| WR12AC32 | 124532 | 1-1/4" | 12' | 100 |



*12 gage, 9gage, 8gage prettied wires are available
* Other angle clip pins, angle clips and eyelag screws can be prettied


12 gage galvanized soft straight cut wires

| MODEL NO. | CAT. NO. | WIRE LENGTH | QTY./ BUNDLE |
|-----------|----------|-------------|--------------|
| WRSC04 | 124104 | 4' | 100 |
| WRSC06 | 124106 | 6' | 100 |
| WRSC08 | 124108 | 8' | 100 |
| WRSC10 | 124110 | 10' | 101 |
| WRSC12 | 124112 | 12' | 102 |
| WRSC14 | 124114 | 14' | 103 |
| WRSC16 | 124116 | 16' | 104 |
| WRSC18 | 124118 | 18' | 105 |
| WRSC20 | 124120 | 20' | 106 |

*12 gage, 9gage, 8gage prettied wires are available

12 GAGE PRE-TIED WIRE

| WIRE SIZE | VARIATION TOLERANCE | TENSILE RANGE | ZINC PLATED | LENGTHS AVAILABLE | STANDARD |
|-----------|---------------------|---------------|--------------------|-----------------------------|--------------|
| .105" | +/- .003" | 75ksi max. | > 25g/square meter | 2', 3', 4', 6', 8'20' | ASTM A641-92 |



*12 gage double pre-tied wire is also available.
*9 gage pre-tied wire is also available.
*Straight cut wire is also available in different sizes.

*12 gage double pre-tied wire is also available.
*9 gage pre-tied wire is also available.
*Straight cut wire is also available in different sizes.

ATTACHMENTS

| MODEL NO. | DESCRIPTION | MODEL NO. | DESCRIPTION | MODEL NO. | DESCRIPTION |
|--------------|--------------------------------|--------------|--------------------------------|---------------|------------------------------|
| PDAC90-25F10 | 1" pin with 90° angle clip | PDAC45-25F10 | 1" pin with 45° angle clip | PDACH90-22F10 | 7/8" pin with 90° angle clip |
| PDAC90-32F10 | 1-1/4" pin with 90° angle clip | PDAC45-32F10 | 1-1/4" pin with 45° angle clip | | |



| MODEL NO. | DESCRIPTION | MODEL NO. | MODEL NO. | MODEL NO. | MODEL NO. |
|-----------|----------------|-----------|-----------|-----------|---------------|
| CL-1 | 90° angle clip | VOH-14 | 750SD | ADOC-14 | Eye lag Screw |



| MODEL NO. | MODEL NO. | DESCRIPTION |
|-------------|----------------------|--------------------------|
| Toggle Bolt | Timber w/ angle clip | Timber pin w/ angle clip |



PACKAGING

| | |
|---|--|
| 100pc/Tube bundle, 100pcs angle clip at one side | 100pc/Barbell bundle, 50pcs angle clip at each side |
|---|--|



20 bundles/master bundle

20 bundles/master bundle
with bag and lifting loops



Bundles in Crate

Bundles in Crate





POWDER ACTUATED FASTENING SYSTEMS

Blue Point Fasteners

Tel: 1-877-779-2583

Fax: 1-866-672-9402

Email: info@bpfasteners.com

14728 Yorba Court
Chino, CA 91710 USA

www.bpfasteners.com

